

Automatic Strapping Machine
Stand Model WG-22XN



FEATURES:

- 1.Rapid speed: 2.0sec/per cycle, 30cycles/per min.
- 2.Easy Maintenance: No Greasing, Mechanism is stable and durable, Easy operation.
- 3.Tension Adjustment: Can be adjustable at well,Max. tension is over 90kgs.
- 4.Precision Structure: Main machine's component is made of aluminum alloy. Control System is compatible.
- 5.Add on a safety device, built for 24 hrs continuous operation.
- 6.Easy loading or unloading: To load or unload the strapping roll is convenient due to the dispenser is placed outside.
- 7.Extensive applications: can be independent operation or combine with other machines for unmanned
- 8.Electric appliance adopted: PLC control, French TEI and photoelectric switch control(WG-22XA)
- 9.Optional: any arch size

Model	WG-22XN
Strapping tension	40-700Nadjustable
Strapping speed	2.0Sec./Strap
Strap width	8-19mm
Arch size	800x600mm
Power supply	380V/50-60Hz, 220V
Power consumption	0.85KVA
Machine size	1410X600X1540mm
Machine weight	250kg

Automatic Strapping Machine
Vertical Model DBA-130A



Model	DBA-130A
Strapping tension	100-700Nadjustable
Strapping speed	2.0Sec./Strap
Strap width	9-15mm
Chute size	L 1000mm
Power supply	110,220V/50-60Hz
Power consumption	0.5KVA
Machine size	1860X560X1500mm
Machine weight	140kg

Semi-Automatic Strapping Machine
KZBI



Detailed Product Description

Features:

- 1) Strapping tension: 5 - 60kg
- 2) Strapping speed: 2.0sec./strap
- 3) Strap width: 6 - 15mm
- 4) Controlled PP strap cooling time, which can make PP strap to fasten well in any time
- 5) Electricity saving device, the motor automatically stops running after 35 sec. and pauses to reduce normal wearing and to prolong the m/c life
- 6) With non-fast heater plate, it will increase the work efficiency
- 7) Advanced P.C.B microchip circuit board control system
- 8) Less malfunction and easy maintenance
- 9) Standard accessories, stable quality and durable material

Outer packing:

Carton dimensions: 920 x 600 x 860mm

N.W.: 90kg

G.W.: 105kg

Model	KZB-I
Strapping tension	40-480Nadjustable
Strapping speed	2.2Sec./Strap
Strap width	6-15mm
Power supply	110V, 220-240V/50-60Hz
Power consumption	0.4KVA
Machine size	835X560X725mm
Machine weight	90kg